



Z-Wave Protocol Implementation Conformance Statement

Siren Gen5

General Information

Product Identifier:	ZW080-A17
Brand Name:	Aeotec
Product Version:	HW: 50 FW: 3.25
Z-Wave Certification #:	ZC10-14090012

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	Yes
Supports Security S2?	No
SmartStart Compatible?	No

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0x0050
Z-Wave Product Type:	0x0104
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.51.01
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	Siren / Always On Slave

Association Group Information

Group # / Max Description

Nodes

1 / 5	Group 1 is assigned to the Lifeline association group and every device has 5 nodes to associate. When the Siren is received the commands sent by controller to be turned on or off, the Siren will send a basic report of its status to the nodes in association group 1. To change what kind of signal is sent to the nodes in group 1, please see the detailed description of configuration parameter 80.
-------	---

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Siren Gen5

Supported Command Classes (16):

Association Group Information V1

Command Class Basic

Command Class Device Reset Locally

Command Class Manufacturer Specific

Command Class Scene Activation

Command Class Security

Command Class Switch Binary

Command Class Version

Command Class Association

Command Class Configuration

Command Class Firmware Update Md

Command Class Powerlevel

Command Class Scene Actuator Conf

Command Class Switch All

Command Class Switch Multilevel

Command Class Z-Wave+ Info

Controlled Command Classes (2):

Command Class Hail

Command Class Scene Activation