



## Z-Wave Protocol Implementation Conformance Statement

### Qubino Flush 1D relay

#### General Information

**Product Identifier:** ZMNHN  
**Brand Name:** QUBINO  
**Product Version:** 01  
**Z-Wave Certification #:** ZC10-15070017

#### Z-Wave Product Information

Supports Z-Wave Beaming Technology? Yes  
Supports Z-Wave Network Security? Yes  
Supports Z-Wave AES-128 Security S0? No  
Supports Security S2? No  
SmartStart Compatible? No

#### Z-Wave Technical Information

**Z-Wave Frequency:** CEPT (Europe)  
**Z-Wave Product ID:** 0x0053  
**Z-Wave Product Type:** 0x0002  
**Z-Wave Hardware Platform:** ZM5202  
**Z-Wave Development Kit Version:** 6.51.06  
**Z-Wave Library Type:** Enhanced 232 Slave  
**Z-Wave Device Type / Role Type:** On/Off Power Switch / Always On Slave

#### Association Group Information

Group # / Max	Description
<b>Nodes</b>	
1 / 1	Group 1: Lifeline group (reserved for communication with the main controller), 1 node allowed.
2 / 16	Group 2: basic on/off (triggered at change of the output state and reflecting its state) up to 16 nodes.
3 / 16	Group 3: basic on/off (triggered at change of the input I2 state and reflecting its state) up to 16 nodes.
4 / 16	Group 4: Binary Sensor Report (triggered at change of the input I2 state and reflecting its state) up to 16 nodes.

# Z-Wave Protocol Implementation Conformance Statement

**(Continued)**

## Qubino Flush 1D relay

5 / 16            Group 5: Notification Report (triggered at change of the input I2 state and reflecting its state) up to 16 nodes.