

Z-Wave Protocol Implementation Conformance Statement

Qubino Flush 2 relays

General Information

Product Identifier:	ZMNHB
Brand Name:	QUBINO
Product Version:	App: 5.0
Z-Wave Certification #:	ZC10-15100010

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	No
SmartStart Compatible?	No

Z-Wave Technical Information

Z-Wave Frequency:	CEPT (Europe)
Z-Wave Product ID:	0x0051
Z-Wave Product Type:	0x0002
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.51.06
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	On/Off Power Switch / Always On Slave

Association Group Information

Group # / Max	Description
Nodes	
1 / 1	Lifeline group (reserved for communication with the main controller), 1 node allowed.
2 / 16	basic on/off (triggered at change of the output Q1 state and reflecting its state) up to 16 nodes.
3 / 16	switch binary report (triggered at change of the output Q1 state and reflecting its state) up to 16 nodes.
4 / 16	power meter report (triggered at change of the output Q1 state) up to 16 nodes.
5 / 16	basic on/off (triggered at change of the output Q2 state and reflecting its state) up to 16 nodes.
6 / 16	switch binary report (triggered at change of the output Q2 state and reflecting its state) up to 16 nodes.

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Qubino Flush 2 relays

- 7 / 16 power meter report (triggered at change of the output Q2 state) up to 16 nodes.
- 8 / 16 multilevel sensor report (triggered at change of temperature sensor) up to 16 nodes.