

Z-Wave Protocol Implementation Conformance Statement

FIBARO Single Switch 2

General Information

Product Identifier:	FGS-213
Brand Name:	FIBARO
Product Version:	HW: 3 FW: 3.2
Z-Wave Certification #:	ZC10-16075135

Product Features

Switch Load Capacity Watts up to 1920W

Switch Load Capacity Volt-Ampere

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	No
SmartStart Compatible?	No

Z-Wave Technical Information

Z-Wave Frequency:	CEPT (Europe)
Z-Wave Product ID:	0x1000
Z-Wave Product Type:	0x0403
Z-Wave Hardware Platform:	ZM5101
Z-Wave Development Kit Version:	6.51.06
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	On/Off Power Switch / Always On Slave

Association Group Information

Group # / Max	Description
Nodes	
1 / 1	"Lifeline" reports the device status and allows for assigning single device only (main controller by default).
2 / 5	"On/Off (S1)" is assigned to switch connected to the S1 terminal (uses Basic command class).

Z-Wave Protocol Implementation Conformance Statement

(Continued)

FIBARO Single Switch 2

- 3 / 5 "Dimmer (S1)" is assigned to switch connected to the S1 terminal (uses Switch Multilevel command class).
- 4 / 5 "On/Off (S2)" is assigned to switch connected to the S2 terminal (uses Basic command class).
- 5 / 5 "Dimmer (S2)" is assigned to switch connected to the S2 terminal (uses Switch Multilevel command class).

Controlled Command Classes (3):

Basic

Notification V5

Switch Multilevel V3