

Z-Wave Protocol Implementation Conformance Statement

Z-Wave Interface Module

General Information

| | |
|--------------------------------|------------------------|
| Product Identifier: | Pro.zwi.il |
| Brand Name: | Pro Control |
| Product Version: | HW: 193 FW: 4.36:01.01 |
| Z-Wave Certification #: | ZC10-16085177 |

Product Features

| | |
|---|-----------------------------------|
| Color | Black |
| Communications Connections | Ethernet (Wired) |
| Communications Protocol | Manufacturer Proprietary Protocol |
| Controller Supports Multiple Networks | No |
| Controller Supports Multiple Z-Wave Interfaces | No |
| Firmware Updatable | Updatable by Consumer by Wire |
| IP (Ingress Protection) Rated | No |
| Outdoor Use | No |

Z-Wave Product Information

| | |
|--------------------------------------|-----|
| Supports Z-Wave Beaming Technology? | Yes |
| Supports Z-Wave Network Security? | Yes |
| Supports Z-Wave AES-128 Security S0? | Yes |
| Supports Security S2? | No |
| SmartStart Compatible? | No |

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Z-Wave Interface Module

Z-Wave Technical Information

| | |
|--|-------------------------------------|
| Z-Wave Frequency: | Israel |
| Z-Wave Product ID: | 0x0001 |
| Z-Wave Product Type: | 0x0001 |
| Z-Wave Hardware Platform: | ZM5304 |
| Z-Wave Development Kit Version: | 6.51.07 |
| Z-Wave Library Type: | Static Controller |
| Z-Wave Device Type / Role Type: | Gateway / Central Static Controller |

Association Group Information

Group # / Max **Description**

Nodes

1 / 1 Z-Wave Plus Lifeline

Supported Command Classes (10):

| | |
|----------------------|----------------------------------|
| Application Status | Association Group Information V2 |
| Association V2 | CRC16 Encapsulation |
| Device Reset Locally | Manufacturer Specific V2 |
| Powerlevel | Security S0 |
| Version V2 | Z-Wave Plus Info V2 |

Controlled Command Classes (37):

| | |
|----------------------------------|------------------------------|
| Association Group Information V2 | Association V2 |
| Barrier Operator | Basic V2 |
| Battery | Configuration V3 |
| CRC16 Encapsulation | Door Lock V3 |
| Indicator | Manufacturer Specific V2 |
| Meter V4 | Multi-Channel Association V3 |
| Multi-Channel V4 | Network Management Basic |
| Network Management Inclusion | Network Management Primary |
| Network Management Proxy | No Operation |
| Notification V3 | Powerlevel |
| Scene Activation | Scene Actuator Conf |
| Scene Controller Conf | Security S0 |
| Switch All | Switch Binary V2 |
| Switch Multilevel V4 | Thermostat Fan Mode V4 |
| Thermostat Fan State V2 | Thermostat Mode V3 |
| Thermostat Operating State V2 | Thermostat Setpoint V3 |
| Time Parameters | Time V2 |
| User Code | Version V2 |
| Wake Up V2 | |