

Z-Wave Protocol Implementation Conformance Statement

Multisensor

General Information

Product Identifier:	HKZW-MS01
Brand Name:	Hank
Product Version:	HW: 1 FW: 1.04
Z-Wave Certification #:	ZC10-17045529

Product Features

Firmware Updatable	Updatable by Consumer by RF
Sensors	Humidity Luminance Motion/No Motion (Binary)
Supported Notification Types	Access Control
Battery Type	CR123A
Color	White
Battery Quantity	2

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	No
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	Yes
Supports Security S2?	No
SmartStart Compatible?	No

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Multisensor

Z-Wave Technical Information

Z-Wave Frequency:	CEPT (Europe)
Z-Wave Product ID:	0x0006
Z-Wave Product Type:	0x0200
Z-Wave Hardware Platform:	ZM5101
Z-Wave Development Kit Version:	6.51.09
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	Notification Sensor / Reporting Sleeping Slave

Association Group Information

Group # / Max Description

Nodes

1 / 5	1. Notification Report. Sensor will send Notification Report to the associated nodes when Multisensor is removed or/and PIR is triggered. 2. Sensor Multilevel Report. Multisensor will send Sensor Multilevel Report to the associated nodes at setting interval. 3. Battery Report. Multisensor will send Battery Report when the battery level is low and the battery report's value is 0xFF. 4. Device Reset Locally Notification.
2 / 5	1. Basic Set Multisensor will send Basic Set to associated nodes when the PIR is triggered.

Supported Command Classes (14):

Association Group Info	Association V2
Battery	Configuration
Device Reset Locally	Firmware Update Meta-Data V2
Manufacturer Specific V2	Notification V5
Powerlevel	Security S0
Sensor Multilevel V5	Version V2
Wake Up V2	Z-Wave Plus Info V2

Controlled Command Classes (1):

Basic