



Z-Wave Protocol Implementation Conformance Statement

Plug

General Information

Product Identifier: FT096-B09
Brand Name: Oomi
Product Version: HW: 96 FW: 1.05
Z-Wave Certification #: ZC10-17045558

Product Features

Supported Meter Type Electric Energy

Electric Load Type Dimmable LED
ELV (Electronic)
Fluorescent
Incandescent
Inductive (e.g. Motor)
LED
MLV (Magnetic)

Firmware Updatable Updatable by Consumer by RF

Z-Wave Product Information

Supports Z-Wave Beaming Technology? Yes
Supports Z-Wave Network Security? Yes
Supports Z-Wave AES-128 Security S0? Yes
Supports Security S2? No
SmartStart Compatible? No

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Plug

Z-Wave Technical Information

Z-Wave Frequency:	Australia / New Zealand
Z-Wave Product ID:	0x0060
Z-Wave Product Type:	0x0203
Z-Wave Hardware Platform:	ZM5101
Z-Wave Development Kit Version:	6.51.09
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	On/Off Power Switch / Always On Slave

Association Group Information

Group # / Max Description

Nodes

1 / 5	Z-Wave Plus Lifeline. The Hial CC and Basic Report CC (configured by parameter 80) can be sent to the associated nodes in this group.
2 / 5	Forward the Basic Set, Switch Binary Set to associated nodes in Group 2 when the Plug receives the Basic Set, Switch Binary Set commands from the main controller.

Supported Command Classes (15):

Association Group Info	Association V2
Basic	Clock
Configuration	Device Reset Locally
Firmware Update Meta-Data V2	Manufacturer Specific V2
Meter V3	Powerlevel
Security S0	Switch All
Switch Binary	Version V2
Z-Wave Plus Info V2	

Controlled Command Classes (3):

Basic	Hail
Switch Binary	