



Z-Wave Protocol Implementation Conformance Statement

Beanbag Thermostat Receiver

General Information

Product Identifier:	MAX10Z-737
Brand Name:	Beanbag
Product Version:	HW: 2 FW: 2.00
Z-Wave Certification #:	ZC10-17055592

Product Features

Switch Type	Push Button
Load Capacity Current	3 Amp
Loads Controlled	2
Thermostat Modes	Heat
Color	White
Neutral Wire Required	Yes
Firmware Updatable	Updatable by Consumer by RF
Thermostat HVAC Systems Supported	Heat Only
Sensors	Air Temperature

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	No
SmartStart Compatible?	No

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Beanbag Thermostat Receiver

Z-Wave Technical Information

Z-Wave Frequency:	CEPT (Europe)
Z-Wave Product ID:	0x0001
Z-Wave Product Type:	0x0014
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.61.00
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	Thermostat - HVAC / Always On Slave

Association Group Information

Group # / Max Description

Nodes

1 / 1 Z-Wave Plus Lifeline

Supported Command Classes (19):

Alarm V1	Association Group Information V1
Association V2	Basic V1
Binary Switch V1	Configuration V1
Device Reset Local V1	Firmware Update MD V2
Manufacturer Specific V2	Multi-Channel Association V2
Multi-Channel V4	Multilevel Sensor V1
Powerlevel	Schedule V1
Thermostat Mode V1	Thermostat Operating State V1
Thermostat Setpoint V1	Version V2
Z-Wave Plus Info V2	

Controlled Command Classes (1):

Time V1