

Z-Wave Protocol Implementation Conformance Statement

Plug

General Information

Product Identifier:	FT145-K19
Brand Name:	Oomi
Product Version:	HW: 145 FW: 1.00
Z-Wave Certification #:	ZC10-17095766

Product Features

Electric Load Type	Dimmable LED ELV (Electronic) Fluorescent Incandescent Inductive (e.g. Motor) LED MLV (Magnetic)
Firmware Updatable	Updatable by Consumer by RF
Supported Meter Type	Electric Energy

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	Yes
Supports Security S2?	No
SmartStart Compatible?	No

Z-Wave Technical Information

Z-Wave Frequency:	China
Z-Wave Product ID:	0x0091
Z-Wave Product Type:	0x1D03
Z-Wave Hardware Platform:	ZM5101
Z-Wave Development Kit Version:	6.51.09
Z-Wave Library Type:	Enhanced 232 Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Plug

Association Group Information

Group # / Max **Description**

Nodes

1 / 5 Z-Wave Plus Lifeline. The Hial CC and Basic Report CC (configured by parameter 80) can be sent to the associatd nodes in this group.

2 / 5 Forward the Basic Set, Switch Binary Set to associated nodes in Group 2 when the Plug receives the Basic Set, Switch Binary Set commands from the main controller.

Supported Command Classes (17):

Association Group Info	Association V2
Basic	Clock
Configuration	Device Reset Locally
Firmware Update Meta-Data V2	Manufacturer Specific V2
Meter V3	Powerlevel
Security S0	Switch All
Switch Binary	Switch Color
Switch Multilevel V2	Version V2
Z-Wave Plus Info V2	

Controlled Command Classes (3):

Basic	Hail
Switch Binary	