



Z-Wave Protocol Implementation Conformance Statement

Door/Window Sensor

General Information

Product Identifier: T8342
Brand Name: Axis Communications
Product Version: HW: 1 FW: 1.01:00.01
Z-Wave Certification #: ZC10-17115881

Product Features

Battery Quantity 2
Battery Type CR2450
Color White
Firmware Updatable Updatable by Consumer via Internet
Supported Notification Types Access Control

Z-Wave Product Information

Supports Z-Wave Beaming Technology? No
Supports Z-Wave Network Security? Yes
Supports Z-Wave AES-128 Security S0? Yes
Supports Security S2? Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible? No

Z-Wave Technical Information

Z-Wave Frequency: U.S. / Canada / Mexico
Z-Wave Product ID: 0x0001
Z-Wave Product Type: 0x0003
Z-Wave Hardware Platform: SD3502
Z-Wave Development Kit Version: 6.71.01
Z-Wave Library Type: Enhanced 232 Slave
Z-Wave Device Type / Role Type: Notification Sensor / Reporting Sleeping Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Door/Window Sensor

Association Group Information

Group # / Max Description

Nodes

- 1 / 1 Association with 1 node.
- 2 / 4 Association with 4 nodes.

Supported Command Classes (15):

- | | |
|--------------------------------------|--|
| Command Class Association Group Info | Command Class Association V2 |
| Command Class Battery | Command Class Device Reset Locally |
| Command Class Firmware Update Md V4 | Command Class Manufacturer Specific V2 |
| Command Class Notification V4 | Command Class Powerlevel |
| Command Class Security | Command Class Security 2 |
| Command Class Supervision | Command Class Transport Service V2 |
| Command Class Version V2 | Command Class Wake Up V2 |
| Command Class Z-Wave+ Info V2 | |

Controlled Command Classes (1):

- Command Class Basic