

Z-Wave Protocol Implementation Conformance Statement

Power On/Off Plug

General Information

Product Identifier:	T8344-JP
Brand Name:	Axis Communications
Product Version:	HW: 1 FW: 1.01:00.01
Z-Wave Certification #:	ZC10-18015972

Product Features

Firmware Updatable	Updatable by Consumer via Internet
Switch Load Capacity Current	12
Switch Load Capacity Volt-Ampere	100
Sensors	Power
Supported Notification Types	Power Management
Color	White
Electric Load Type	Incandescent LED
Switch Load Capacity Watts	1200

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	Yes
Supports Security S2?	Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible?	No

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Power On/Off Plug

Z-Wave Technical Information

Z-Wave Frequency:	Japan
Z-Wave Product ID:	0x0001
Z-Wave Product Type:	0x0004
Z-Wave Hardware Platform:	SD3502
Z-Wave Development Kit Version:	6.71.01
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	On/Off Power Switch / Always On Slave

Association Group Information

Group # / Max **Description**

Nodes

1 / 1	Association with 1 node.
2 / 4	Association with 4 nodes (i.e. end devices such as detectors or other lighting switches). This allows the On/Off module to receive commands directly from these end devices without the participation of the controller.

Supported Command Classes (16):

Association Group Info	Association V2
Basic	Configuration
Device Reset Locally	Firmware Update Meta-Data V4
Manufacturer Specific V2	Notification V4
Powerlevel	Security S0
Security S2	Supervision
Switch Binary	Transport Service V2
Version V2	Z-Wave Plus Info V2

Controlled Command Classes (1):

Basic