

Z-Wave Protocol Implementation Conformance Statement

Z-Wave In-Wall On/Off Switch

General Information

Product Identifier:	WS-100
Brand Name:	ZLINK
Product Version:	HW: 255 FW: 50.03
Z-Wave Certification #:	ZC10-18025995

Product Features

Color	White
Outdoor Use	No
Z-Wave Scene Type	Scene & Central Scene
Firmware Updatable	Updatable by Consumer by RF
Neutral Wire Required	Yes
Switch Load Capacity Volt-Ampere	120VAC
Switch Type	Decorator Paddle Rocker
Switch Load Capacity Watts	1800W resistive load
Switch Load Capacity Current	15Amps
Electric Load Type	Fluorescent Incandescent LED

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	Yes: S2 Authenticated, S2 Unauthenticated

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Z-Wave In-Wall On/Off Switch

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0x3033
Z-Wave Product Type:	0x4447
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.81.00
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	On/Off Power Switch / Always On Slave

Association Group Information

Group # / Max Description

Nodes

1 / 5 1. Z-Wave Plus Lifeline 2. Central Scene Notification 3. Switch Binary Report 4. Device Reset Locally
Notification

Supported Command Classes (17):

Association Group Info	Association V2
Basic	Central Scene V3
Configuration V3	Device Reset Locally
Firmware Update Meta-Data V4	Manufacturer Specific
Powerlevel	Scene Activation
Scene Actuator Conf	Security S2
Supervision	Switch Binary
Transport Service V2	Version V2
Z-Wave Plus Info V2	

Controlled Command Classes (2):

Central Scene V3	Supervision
------------------	-------------