

Z-Wave Protocol Implementation Conformance Statement

Z-Wave Metering Plug Smart Start

General Information

Product Identifier:	POPE700397
Brand Name:	Popp & Co.
Product Version:	HW: 1 FW: 3.01
Z-Wave Certification #:	ZC10-18026015

Product Features

Sensors	Voltage
Electric Load Type	Dimmable ELV (Magnetic) Dimmable Fluorescent Dimmable LED Dimmable MLV (Magnetic) ELV (Electronic) Fluorescent Incandescent Inductive (e.g. Motor) LED
Outdoor Use	Yes
Switch Load Capacity Watts	3500
Supported Meter Type	Electric Energy
IP (Ingress Protection) Rated	Yes
Firmware Updatable	Updatable by Consumer by RF
Color	White

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Z-Wave Metering Plug Smart Start

Z-Wave Technical Information

Z-Wave Frequency:	CEPT (Europe)
Z-Wave Product ID:	0x000A
Z-Wave Product Type:	0x0003
Z-Wave Hardware Platform:	ZM5101
Z-Wave Development Kit Version:	6.81.00
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	On/Off Power Switch / Always On Slave

Association Group Information

Group # / Max **Description**

Nodes

1 / 5 Z-Wave Plus Lifeline

2 / 5 Control other devices on single click of the button. BASIC command (on/off) is sent according to switching state of the load.

Supported Command Classes (19):

Association Group Info	Association V2
Basic	Central Scene V3
Configuration	Device Reset Locally
Firmware Update Meta-Data V4	Manufacturer Specific V2
Meter V4	Multi-Channel Association V3
Powerlevel	Protection
Security S2	Sensor Multilevel V8
Supervision	Switch Binary
Transport Service V2	Version V3
Z-Wave Plus Info V2	

Controlled Command Classes (1):

Basic