

Z-Wave Protocol Implementation Conformance Statement

Direct-Wire Outdoor Smart Switch (40 Amp)

General Information

Product Identifier:	14285/ZW4007
Brand Name:	GE
Product Version:	HW: 255 FW: 5.53
Z-Wave Certification #:	ZC10-18056123

Product Features

Firmware Updatable	Updatable by Consumer by RF
Switch Load Capacity Current	40
Loads Controlled	2
Outdoor Use	Yes
Supported Meter Type	Electric Energy
Z-Wave Scene Type	Scene & Central Scene

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible?	Yes

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0x3032
Z-Wave Product Type:	0x4F44
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.81.01
Z-Wave Library Type:	Enhanced 232 Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Direct-Wire Outdoor Smart Switch (40 Amp)

Association Group Information

Group # / Max **Description**

Nodes

- 1 / 5 Z-Wave Plus Lifeline, Binary Switch Report
- 2 / 5 Basic Set, controlled by local load
- 3 / 5 Basic Set, controlled by pressing the On or Off button

Supported Command Classes (18):

- | | |
|------------------------------|--------------------------|
| Association Group Info | Association V2 |
| Basic | Central Scene V3 |
| Configuration V3 | Device Reset Locally |
| Firmware Update Meta-Data V4 | Manufacturer Specific V2 |
| Meter V3 | Powerlevel |
| Scene Activation | Scene Actuator Conf |
| Security S2 | Supervision |
| Switch Binary | Transport Service V2 |
| Version V2 | Z-Wave Plus Info V2 |

Controlled Command Classes (1):

- Basic