

Z-Wave Protocol Implementation Conformance Statement

GigaSPIRE MAX

General Information

Product Identifier:	GS2026E
Brand Name:	Calix Inc.
Product Version:	HW: 10 FW: 6.01:01.81:01.00:01.00
Z-Wave Certification #:	ZC10-18106265

Product Features

Color	Gray
Gateway Has Preferred Partners	Yes

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	Yes
Supports Security S2?	Yes: S2 Access Control, S2 Authenticated, S2 Unauthenticated
SmartStart Compatible?	No

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0x07EA
Z-Wave Product Type:	0x4753
Z-Wave Hardware Platform:	ZM5101
Z-Wave Development Kit Version:	6.81.01
Z-Wave Library Type:	Bridge Controller
Z-Wave Device Type / Role Type:	Central Controller / Central Static Controller

Association Group Information

Group # / Max	Description
Nodes	
1 / 5	Z-Wave Plus Lifeline; A Notification frame is sent to the nodes in this association group when a Lifeline event occurs. Notification event clear signal when the Lifeline event is no longer detected.

Z-Wave Protocol Implementation Conformance Statement

(Continued)

GigaSPIRE MAX

Supported Command Classes (14):

Association Group Information V3
CRC16 Encapsulation
Inclusion Controller
Powerlevel
Security S2
Transport Service V2
Z/IP V4

Association V2
Device Reset Locally
Manufacturer Specific V2
Security S0
Supervision
Version V2
Z-Wave Plus Info V2

Controlled Command Classes (14):

Association Group Information V3
Basic
Device Reset Locally
Multi-Channel Association V3
Security S0
Switch Multilevel
Wake Up V2

Association V2
CRC16 Encapsulation
Manufacturer Specific V2
Multi-Channel V4
Security S2
Version V2
Z-Wave Plus Info V2