



Z-Wave Protocol Implementation Conformance Statement

Door/ Window Sensor 6

General Information

Product Identifier: ZW112-H
Brand Name: Aeotec
Product Version: HW: 112 FW: 1.03
Z-Wave Certification #: ZC10-19026370

Product Features

Firmware Updatable Updatable by Consumer by RF
Sensors Open/Closed (Binary)
Color White
Supported Notification Types Access Control

Z-Wave Product Information

Supports Z-Wave Beaming Technology? No
Supports Z-Wave Network Security? Yes
Supports Z-Wave AES-128 Security S0? Yes
Supports Security S2? No
SmartStart Compatible? No

Z-Wave Technical Information

Z-Wave Frequency: Singapore
Z-Wave Product ID: 0x0070
Z-Wave Product Type: 0x1C02
Z-Wave Hardware Platform: ZM5101
Z-Wave Development Kit Version: 6.51.10
Z-Wave Library Type: Enhanced 232 Slave
Z-Wave Device Type / Role Type: Notification Sensor / Reporting Sleeping Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Door/ Window Sensor 6

Association Group Information

Group # / Max **Description**

Nodes

1 / 5 Group 1 is assigned to the Lifeline association group and every device has 5 nodes to associate. The sensor binary report, basic set or notification report command can be sent in this group when the Sensor is triggered.

Supported Command Classes (14):

- | | |
|--|-------------------------------------|
| Command Class Association Group Info | Command Class Association V2 |
| Command Class Battery | Command Class Configuration |
| Command Class Device Reset Locally | Command Class Firmware Update Md V2 |
| Command Class Manufacturer Specific V2 | Command Class Notification V4 |
| Command Class Powerlevel | Command Class Security |
| Command Class Sensor Binary | Command Class Version V2 |
| Command Class Wake Up V2 | Command Class Z-Wave+ Info V2 |

Controlled Command Classes (1):

- Command Class Basic