

Z-Wave Protocol Implementation Conformance Statement

Smart Humidity And Temperature Sensor

General Information

Product Identifier: 51112
Brand Name: CLEVERIO
Product Version: HW: 255 FW: 3.01
Z-Wave Certification #: ZC10-19056481

Product Features

Battery Type CR2450
Color White
Sensors Air Temperature
Humidity
Battery Quantity 1

Z-Wave Product Information

Supports Z-Wave Beaming Technology? No
Supports Z-Wave Network Security? Yes
Supports Z-Wave AES-128 Security S0? No
Supports Security S2? Yes: S2 Unauthenticated
SmartStart Compatible? No

Z-Wave Technical Information

Z-Wave Frequency: CEPT (Europe)
Z-Wave Product ID: 0x1000
Z-Wave Product Type: 0x8007
Z-Wave Hardware Platform: ZM5202
Z-Wave Development Kit Version: 6.71.03
Z-Wave Library Type: Routing Slave
Z-Wave Device Type / Role Type: Notification Sensor / Reporting Sleeping Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Smart Humidity And Temperature Sensor

Association Group Information

Group # / Max **Description**

Nodes

1 / 5 - Lifeline between controller and the product - Supported command classes: Battery Report, Multilevel Sensor Report, and Device Reset Locally notification. - Association Group description Association group 1: Lifeline association group Maximum supported node is 5 Include command classes: Battery report, multilevel sensor report, and Device Reset Locally

Supported Command Classes (14):

- | | |
|--------------------------|------------------------------|
| Association Group Info | Association V2 |
| Battery | Device Reset Locally |
| Manufacturer Specific V2 | Multi-Channel Association V3 |
| Powerlevel | Security S2 |
| Sensor Multilevel V10 | Supervision |
| Transport Service V2 | Version V3 |
| Wake Up V2 | Z-Wave Plus Info V2 |