

Z-Wave Protocol Implementation Conformance Statement

Power Switch Meter

General Information

| | |
|--------------------------------|-------------------|
| Product Identifier: | PSM-29ZW |
| Brand Name: | Climax Technology |
| Product Version: | HW: 255 FW: 4.01 |
| Z-Wave Certification #: | ZC10-19126809 |

Product Features

Firmware Updatable Updatable by Consumer by RF

Switch Load Capacity Watts

Z-Wave Product Information

| | |
|--------------------------------------|-------------------------|
| Supports Z-Wave Beaming Technology? | Yes |
| Supports Z-Wave Network Security? | Yes |
| Supports Z-Wave AES-128 Security S0? | No |
| Supports Security S2? | Yes: S2 Unauthenticated |
| SmartStart Compatible? | Yes |

Z-Wave Technical Information

| | |
|--|------------------------------------|
| Z-Wave Frequency: | CEPT (Europe) |
| Z-Wave Product ID: | 0x0002 |
| Z-Wave Product Type: | 0x0004 |
| Z-Wave Hardware Platform: | ZM5202 |
| Z-Wave Development Kit Version: | 6.81.06 |
| Z-Wave Library Type: | Enhanced 232 Slave |
| Z-Wave Device Type / Role Type: | Sub Energy Meter / Always On Slave |

Association Group Information

| Group # / Max | Description |
|---------------|---|
| Nodes | |
| 1 / 5 | The Switch can be set to send reports to associated Z-Wave devices. It supports one association group with five node support for Grouping 1. For grouping 1, the Switch will report its latest status to Z-Wave |

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Power Switch Meter

Supported Command Classes (14):

Association Group Info
CRC16 Encapsulation
Firmware Update Meta-Data V4
Meter V2
Powerlevel
Supervision
Version V3

Association V2
Device Reset Locally
Manufacturer Specific V2
Multi-Channel Association V3
Security S2
Transport Service V2
Z-Wave Plus Info V2