



Z-Wave Protocol Implementation Conformance Statement

In-Wall Smart Toggle Switch

General Information

Product Identifier: 39354 / 54912 / ZW4009
Brand Name: UltraPro
Product Version: HW: 255 FW: 5.53
Z-Wave Certification #: ZC10-20106984

Product Features

Switch Type	Toggle
Firmware Updatable	Updatable by Consumer by RF
Switch Load Capacity Watts	1800 (resistive)
Neutral Wire Required	Yes
Switch Load Capacity Current	15
Z-Wave Scene Type	Scene & Central Scene

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible?	Yes

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0x3238
Z-Wave Product Type:	0x4952
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.81.03
Z-Wave Library Type:	Enhanced 232 Slave

(Continued)

In-Wall Smart Toggle Switch

Association Group Information

Group # / Max Description

Nodes

- 1 / 5 Association Group 1 supports Lifeline, Binary Switch Report, Central Scene notification
- 2 / 5 Supports Basic Set and is controlled by pressing the ON or OFF button with the local load.
- 3 / 5 Supports Basic Set and is controlled by double pressing the ON or OFF button.

Supported Command Classes (18):

Application Status	Association Group Info
Association V2	Basic V2
Central Scene V3	Configuration V4
Device Reset Locally	Firmware Update Meta-Data V4
Manufacturer Specific V2	Powerlevel
Scene Activation	Scene Actuator Conf
Security S2	Supervision
Switch Binary V2	Transport Service V2
Version V3	Z-Wave Plus Info V2

Controlled Command Classes (1):

- Basic V2