

Z-Wave Protocol Implementation Conformance Statement

Strips Guard 700

General Information

| | |
|--------------------------------|----------------|
| Product Identifier: | 11 01 299 |
| Brand Name: | Sensitive |
| Product Version: | HW: 1 FW: 6.20 |
| Z-Wave Certification #: | ZC12-20120139 |

Product Features

| | |
|---------------------------|-----------------------------|
| Battery Type | Built in 3.0V LiMnO2 |
| Color | White |
| Firmware Updatable | Updatable by Consumer by RF |
| Outdoor Use | Yes |
| Battery Quantity | 1 |

Z-Wave Product Information

| | |
|--------------------------------------|---|
| Supports Z-Wave Beaming Technology? | No |
| Supports Z-Wave Network Security? | Yes |
| Supports Z-Wave AES-128 Security S0? | No |
| Supports Security S2? | Yes: S2 Authenticated, S2 Unauthenticated |
| SmartStart Compatible? | Yes |

Z-Wave Technical Information

| | |
|--|--|
| Z-Wave Frequency: | Hong Kong |
| Z-Wave Product ID: | 0x0004 |
| Z-Wave Product Type: | 0x0004 |
| Z-Wave Hardware Platform: | ZGM130 |
| Z-Wave Development Kit Version: | 7.13.3 |
| Z-Wave Library Type: | Enhanced 232 Slave |
| Z-Wave Device Type / Role Type: | Notification Sensor / Reporting Sleeping Slave |

Z-Wave Protocol Implementation Conformance Statement

(Continued)

Strips Guard 700

Association Group Information

Group # / Max **Description**

Nodes

1 / 1 Strips supports association group 1 (lifeline), max 1 node, normally used to send Strips'notification to the Z-Wave controller.

Supported Command Classes (19):

- | | |
|------------------------------|----------------------------------|
| Application Status | Association Group Information V3 |
| Association V2 | Battery |
| Configuration V4 | Device Reset Locally |
| Firmware Update Meta-Data V5 | Indicator V3 |
| Manufacturer Specific V2 | Multi-Channel Association V3 |
| Notification V8 | Powerlevel |
| Security S2 | Sensor Binary |
| Supervision | Transport Service V2 |
| Version V3 | Wake Up V2 |
| Z-Wave Plus Info V2 | |