

Z-Wave Protocol Implementation Conformance Statement

In-Wall Smart Switch

General Information

Product Identifier:	39348 /54890 /54891/ ZW4008
Brand Name:	UltraPro
Product Version:	HW: 255 FW: 5.54
Z-Wave Certification #:	ZC10-21057028

Product Features

Firmware Updatable	Updatable by Consumer by RF
Neutral Wire Required	Yes
Switch Load Capacity Current	15
Switch Load Capacity Watts	1800
Switch Type	Decorator Paddle Push
Z-Wave Scene Type	Scene & Central Scene

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	Yes
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible?	Yes

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0x3237
Z-Wave Product Type:	0x4952
Z-Wave Hardware Platform:	ZM5202
Z-Wave Development Kit Version:	6.81.04
Z-Wave Library Type:	Enhanced 232 Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

In-Wall Smart Switch

Association Group Information

Group # / Max Description

Nodes

- 1 / 5 Association Group 1 supports Lifeline, Binary Switch Report
- 2 / 5 Association Group 2 supports Basic Set and is controlled by pressing the ON or OFF button with the local load
- 3 / 5 Association Group 3 supports Basic Set and is controlled by double pressing the ON or OFF button

Supported Command Classes (18):

- Application Status
- Association V2
- Central Scene V3
- Device Reset Locally
- Manufacturer Specific V2
- Scene Activation
- Security S2
- Switch Binary V2
- Version V3
- Association Group Info
- Basic V2
- Configuration V4
- Firmware Update Meta-Data V4
- Powerlevel
- Scene Actuator Conf
- Supervision
- Transport Service V2
- Z-Wave Plus Info V2

Controlled Command Classes (1):

- Basic V2