



Z-Wave Protocol Implementation Conformance Statement

Door/Window Sensor

General Information

Product Identifier:	ZSE41
Brand Name:	Zooz
Product Version:	HW: 1 FW: 1.00
Z-Wave Certification #:	ZC12-21080282

Product Features

Firmware Updatable	Updatable by Consumer by RF
Outdoor Use	Yes
Battery Type	CR2032
Battery Quantity	1
Color	White

Z-Wave Product Information

Supports Z-Wave Beaming Technology?	No
Supports Z-Wave Network Security?	Yes
Supports Z-Wave AES-128 Security S0?	No
Supports Security S2?	Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible?	Yes

Z-Wave Technical Information

Z-Wave Frequency:	U.S. / Canada / Mexico
Z-Wave Product ID:	0xE001
Z-Wave Product Type:	0x7000
Z-Wave Hardware Platform:	ZGM130
Z-Wave Development Kit Version:	7.13.9
Z-Wave Library Type:	Enhanced 232 Slave
Z-Wave Device Type / Role Type:	Notification Sensor / Reporting Sleeping Slave

Association Group Information

Group # / Max	Description
Nodes	
1 / 3	The XS Sensor supports Group 1 for Lifeline communication to send open/close notifications.
2 / 5	This device will send a Basic Set command to Group 2 whenever it detects a change in the open/close status. It sends an ON command when OPEN status is detected and OFF command when CLOSED status it detected.

Supported Command Classes (18):

Association Group Information V3	Association V3
Battery	Configuration V4
Device Reset Locally	Firmware Update Meta-Data V5
Indicator V3	Manufacturer Specific V2
Multi-Channel Association V4	Notification V8
Powerlevel	Security S2
Sensor Binary V2	Supervision
Transport Service V2	Version V3
Wake Up V2	Z-Wave Plus Info V2