



Z-Wave Protocol Implementation Conformance Statement

JascoPro Series Z-Wave Plus™ In-Wall Smart Switch, White Toggle,

General Information

Product Identifier: 60517/ZWA4012DV
Brand Name: JascoPro Series
Product Version: HW: 01 FW: 01.21
Z-Wave Certification #: ZC14-22020063

Product Features

Firmware Updatable Updatable by Consumer by RF
Neutral Wire Required Yes
Switch Load Capacity Watts 960W incandescent
Switch Type Toggle
Z-Wave Scene Type Scene & Central Scene

Z-Wave Product Information

Supports Z-Wave Beaming Technology? Yes
Supports Z-Wave Network Security? Yes
Supports Z-Wave AES-128 Security S0? No
Supports Security S2? Yes: S2 Authenticated, S2 Unauthenticated
SmartStart Compatible? Yes

Z-Wave Technical Information

Z-Wave Frequency: U.S. / Canada / Mexico, U.S. / Canada / Mexico, U.S. / Canada / Mexico
Z-Wave Product ID: 0x3338
Z-Wave Product Type: 0x4952
Z-Wave Hardware Platform: ZGM130S037HGN2 / ZGM130S037HGN1
Z-Wave Development Kit Version: 7.15.4
Z-Wave Library Type: Enhanced 232 Slave
Z-Wave Device Type / Role Type: Binary Switch DT / Always On Slave

Z-Wave Protocol Implementation Conformance Statement

(Continued)

JascoPro Series Z-Wave Plus™ In-Wall Smart Switch, White Toggle, 120/277, 700S

Association Group Information

Group # / Max Description

Nodes

1 / 5

2 / 5

3 / 5

Supported Command Classes (19):

- | | |
|--|------------------------------|
| Association Group Information (AGI) V3 | Association V2 |
| Basic V2 | Binary Switch V2 |
| Central Scene V3 | Configuration V4 |
| Device Reset Locally | Firmware Update Meta Data V5 |
| Indicator V3 | Manufacturer Specific V2 |
| Multi Channel Association V3 | Powerlevel |
| Scene Activation | Scene Actuator Configuration |
| Security 2 | Supervision |
| Transport Service V2 | Version V3 |
| Z-Wave Plus Info V2 | |